



**YQK-120**

- Single stage plunger pump, simple structure, reliable performance, interchangeable dies for different size

<b>Technical data</b>	
Crimping range:	Cu10-120mm <sup>2</sup>
Crimping force:	60kN
Stroke:	13mm
Crimping type:	Hexagon Crimping
<b>Accessories:</b>	
Crimping dies:	10,16,25,35,50,70,95,120mm <sup>2</sup>
Sealing O-ring:	One Set

**YQK-240**

- Single stage plunger pump, simple structure, reliable performance, interchangeable dies for different size

<b>Technical data</b>	
Crimping range:	Cu16-240mm <sup>2</sup>
Crimping force:	70kN
Stroke:	18mm
Crimping type:	Hexagon Crimping
<b>Accessories:</b>	
Crimping dies:	16,25,35,50,70,95,120m,150m,185,240mm <sup>2</sup>
Sealing O-ring:	One Set

**KYQ-300C**

SAFETY SYSTEM INSIDE

- With safety valve inside
- With interchangeable dies for different size
- The tool clicks when the pressure reaches its limit
- The head can rotate 180°

<b>Technical data</b>	
Crimping range:	Cu 16-300mm <sup>2</sup>
Crimping force:	100kN
Stroke:	18mm
Crimping type:	Hexagon Crimping
<b>Accessories:</b>	
Crimping dies:	16,25,35,50,70,95,120,150,185,240,300mm <sup>2</sup>
Sealing O-ring:	One Set

**KYQ-400**

SAFETY SYSTEM INSIDE

- With safety valve inside
- With interchangeable dies for different size
- The tool clicks when the pressure reaches its limit
- The head can rotate 180°

<b>Technical data</b>	
Crimping range:	50-400mm <sup>2</sup>
Crimping force:	105kN
Stroke:	32mm
Crimping type:	Hexagon Crimping
<b>Accessories:</b>	
Crimping dies:	50,70,95,120,150,185,240,300,400mm <sup>2</sup>
Sealing O-ring:	One Set



**YQK-300**

- Single stage plunger pump, simple structure, reliable performance, interchangeable dies for different size

<b>Technical data</b>	
Crimping range:	Cu 10-300mm <sup>2</sup>
Crimping force:	70kN
Stroke:	18mm
Crimping type:	Hexagon Crimping
<b>Accessories:</b>	
Crimping dies:	10,16,25,35,50,70,95,120,150,185,240,300mm <sup>2</sup>
Sealing O-ring:	One Set

**KYQ-300**

SAFETY SYSTEM INSIDE

- With safety valve inside
- With interchangeable dies for different size
- The tool clicks when the pressure reaches its limit
- The head can rotate 180°

<b>Technical data</b>	
Crimping range:	Cu 16-300mm <sup>2</sup>
Crimping force:	100kN
Stroke:	21mm
Crimping type:	Hexagon Crimping
<b>Accessories:</b>	
Crimping dies:	16,25,35,50,70,95,120,150,185,240,300mm <sup>2</sup>
Sealing O-ring:	One Set

**FHT-400U**

- U Type of split crimping head, with interchangeable dies
- Suitable for transmission and distribution of indoor and outdoor projects
- The tool work for different kind of connecting and building over head cable

<b>Technical data</b>	
Crimping range:	Cu16-400mm <sup>2</sup>
Crimping force:	120kN
Working pressure:	70Mpa
Stroke:	20mm
<b>Accessories:</b>	
Crimping dies:	16,25,35,50,70,95,120,150,185,240,300,400mm <sup>2</sup>
Sealing O-ring:	One Set
Note: It Can Match Hand Pump	

**FHT-300**

- Split crimping head with interchangeable dies
- Suitable for transmission and distribution of indoor and outdoor projects
- The tool work for different kind of connecting and building over head cable

<b>Technical data</b>	
Crimping range:	16-300mm <sup>2</sup>
Crimping force:	60kN
Stroke:	17mm
Crimping type:	Hexagon Crimping
<b>Accessories:</b>	
Crimping dies:	16,25,35,50,70,95,120,150,185,240,300mm <sup>2</sup>
Sealing O-ring:	One Set
Note: It Can Match Hand Pump	