



**HT-150** SAFETY SYSTEM INSIDE

- Flip top style head, rotates 180°
- With safety valve inside to avoid overload

Technical data	
Crimping range:	Cu 4-150mm <sup>2</sup>
Crimping force:	35kN
Length:	215mm
Crimping type:	Hexagon Crimping
Accessories:	
Crimping dies:	4,6,8,10,16,25,35,50,70,95,120,150mm <sup>2</sup>



**THS-150**

- Flip top style head, rotates 180°
- With safety valve inside to avoid overload

Technical data	
Crimping range:	Cu 10-190mm <sup>2</sup>
Crimping force:	60kN
Accessories:	
Crimping dies:	10-16,25-35,50-70,95-120,150mm <sup>2</sup>



**CYO-510B** SAFETY SYSTEM INSIDE

- Two stage hydraulic system with fast feed and power stroke, With Safety valve, twist the active handle to release the pressure

Technical data	
Crimping force:	126kN
Crimping range:	Cu 50-400mm <sup>2</sup>
Stroke:	38mm
Oil capacity:	145cc
Accessories:	
Crimping dies:	50,70,95,120,150,185,240,300,400mm <sup>2</sup>



**CYO-400C** FLIP TOP STYLE HEAD

- Two stage hydraulic system with fast feed and power stroke

Technical data	
Crimping force:	126kN
Crimping range:	Cu 16-400mm <sup>2</sup>
Stroke:	25mm
Oil capacity:	145cc
Accessories:	
Crimping dies:	16,25,35,50,70,95,120,150,185,240,300,400mm <sup>2</sup>



**CYO-6B** Up to 240mm<sup>2</sup>

- Quad-point indent crimping feature, no die required
  - The head can rotate 350°
  - With Safety valve, twist the active handle to release the pressure
- Suitable for crimping tubular cable lugs and connectors' standard type" and fine and superfine stranded conductors to 240mm<sup>2</sup>

Technical data	
Crimping range:	Cu 10-240mm <sup>2</sup>
Crimping force:	60kN
Stroke:	35mm



**CYO-430** SAFETY SYSTEM INSIDE

- Two stage hydraulic system with fast feed and power stroke, With Safety valve, twist the active handle to release the pressure

Technical data	
Crimping force:	116kN
Crimping range:	Cu 50-400mm <sup>2</sup>
Stroke:	30mm
Oil capacity:	145cc
Accessories:	
Crimping dies:	50,70,95,120,150,185,240,300,400mm <sup>2</sup>



**YQK-70**

- Single stage plunger pump, simple structure, reliable performance, interchangeable dies for different size

Technical data	
Crimping range:	Cu 4-70mm <sup>2</sup>
Crimping force:	45kN
Stroke:	11mm
Crimping type:	Hexagon Crimping
Accessories:	
Crimping dies:	4, 6, 8, 10, 16, 25, 35, 50, 70mm <sup>2</sup>
Sealing O-ring:	One Set



**YYQ-120A**

- Single stage plunger pump, simple structure, reliable performance, interchangeable dies for different size

Technical data	
Crimping range:	Cu 10-120mm <sup>2</sup>
Crimping force:	60kN
Stroke:	13mm
Crimping type:	Hexagon Crimping
Accessories:	
Crimping dies:	10,16,25,35,50,70,95,120mm <sup>2</sup>
Sealing O-ring:	One Set