

▼ Shown: Grip Puller Set BHP351G



## BHP Series



Capacity:

**13, 22, 33 and 45 ton**

Reach:

**252 - 700 mm**

Spread:

**249 - 1100 mm**

Maximum Operating Pressure:

**700 bar**

### Ordering Example

#### Model Number BHP251G:

includes Grip Puller BHP252 and a full hydraulic set. (Hand pump, cylinder, saddle, hose, gauge and gauge adaptor).

#### Model Number BHP252:

includes Grip Puller mechanical parts only, for use with your existing hydraulics.

- Precise hydraulic control allows fast, efficient and safe pulling
- High quality, forged steel components provide superior reliability and service
- Available with and without full hydraulic set.

### ▼ SELECTION CHART

Grip Puller Set Capacity **		13 ton	22 ton	33 ton	45 ton ***
Model Number ►		<b>BHP152 <sup>1)</sup></b>	<b>BHP251G</b>	<b>BHP351G</b>	<b>BHP551G</b>
Included Hydraulics					
Set Weight ►		22 kg	56 kg	91 kg	160 kg
• Hand Pump		P142	P392	P392	P80
• Cylinder		RWH121900	RCH202	RCH302	RCH603
• Saddle		-	HP2015	HP3015	HP5016
• Hose		HC7206C	HC7206C	HC7206C	HC7206C
• Gauge + Adaptor		GA45GC	GA45GC	GA45GC	GA45GC
<b>10</b> Grip Puller	Model Number ►	<b>BHP1762 *</b>	<b>BHP252 *</b>	<b>BHP352 *</b>	<b>BHP552 *</b>
Maximum Spread (mm)	2-jaw	249	400	593	899
	3-jaw	249	499	800	1100
Maximum Reach (mm)	2-jaw	252	300	387	700
	3-jaw	252	300	387	700
Jaw (mm)	Thickness	15	20	24	30
	Width	23	27	38	39
Adjusting Screw (mm)	Thread	¾" - 16 UNF	1" - 8 UNC	1¼" - 7 UNC	1½" - 5.5 UNS
	Length	400	670	790	975
• Case		CW166	CW166	CW350	CW750

<sup>1)</sup> Includes Adaptor FZ1055.

\* Grip Puller order number without hydraulics.

\*\* See warning on page 158.

\*\*\* Puller capacity at 540 bar; maximum cylinder capacity at 700 bar is 60 ton.